

ANTI SLIP POWDER

NON SLIP ADDITIVE FOR SEALERS AND PAINTS.

DESCRIPTION

Anti Slip Powder is a fine polyethylene particle designed to add texture to the finish coats of sealers and floor coatings.

Anti Slip Powder is an easily dispersible powder designed to neither settle or float in a range of sealers and coatings.

USEAGE INSTRUCTIONS

Add to final coat of sealer or paint only

Anti Slip Powder should be slowly poured into the coating while briskly stirring. The sealer or coating may require the addition of a small amount of carrier (eg water for water based paints/sealers and solvent for solvent based sealers/coatings) to make application easier. Trial rates of addition are recommended to test the effect on clarity and surface texture. Adding more powder will improve slip resistance but may make clear coatings hazy if too much is added. Suggested rates of addition are as follows:

Solvent Based Sealers

Add from 200g – 400g per 15ltr pail.

Water Based Paving Paints

Add from 150g – 300g per 15ltr pail.

Varnishes and Clear Sealers

Test at low levels first. Add from 50g – 250g per 15ltr pail.

If Anti Slip is difficult to disperse add small amounts of carrier (ie water or solvent) until the coating flows easily.

Add just before use and stir regularly to ensure even dispersion. Avoid excessive strokes and pressure when using a brush (eg cutting in lines) as this may leave a visible texture line. Discard unused sealer or paint with Anti Slip Powder – do not return to pail. Do not leave anti slip powder in solvent sealers or paints for long periods as this may cause clumping or softening of the particles.

Not suitable for use in spray equipment – brush or roller application only.

PRODUCT USES

- Reduce slip hazard on wet surfaces
- Create texture in final coat of sealers

PRODUCT FEATURES

- May be used on both solvent and water based coatings/sealers
- Easily Dispersed
- Minimal effect on optical clarity
- Improves abrasion resistance of surfaces

TRANSPORT / STORAGE

Pail Sizes	200g Bag, 5kg Pail
Weights	205g, 5.5kg
Dangerous Goods Class	N/A

DISCLAIMER

Customers are advised to consider the information in this data sheet in the context of how the product will be used, including surfaces and any other products used. The information provided in this data sheet represents our best scientific and practical knowledge. Any advice, information or assistance provided by Shalex in relation to its products is given in good faith, however is provided without liability or responsibility. Due to the wide variety of site conditions we are unable to assume liability for any loss that may arise from the use of our products. The user is responsible for checking the suitability of products for their intended use.

Shalex Industries Technical Support Line

1300 720 535